

Key information:

- Cut 2, 15 gauge Polyester outer liner with a 7 gauge Acrylic-loop Thermal inner liner
- Fully coated in Smooth Latex, finished with a Sandy Latex palm dip
- Suitable for use inside or outside, in wet or dry; cold or warm conditions

- Superb wet or dry grip
- Extremely comfortable and dexterous
- Elasticated cuff with coloured cuff size indicator
- Contact Cold Level 2



Code: WS4

Liner: Polyester/
Acrylic

Size: 7 to 11

Gauge: 15/7

Coating: Sandy Latex

Pack size: 10 pairs

Carton: 120 pairs

EN388: 2242B

EN407: X2XXXX

EN511: X21

Applications include:

Construction, Scaffolding, Infrastructure, Banksmen, Engineering, Landscaping, Cold Stores and Refrigeration

Limitations of Use

Maintenance Examine gloves for damages, splits and holes before each use. Always replace damaged gloves. Only properly fitting gloves guarantee protection and grip.

Storage Store at normal room temperature in a dry, well ventilated area. Avoid direct heat radiation.

Disposal Used gloves can be contaminated. Dispose with household waste or as instructed by your local authority.

Cleaning Do not wash. The performance of the product after laundering is unknown. Beat or brush out after each use, depending on level of dirt.

DurabilityThe period of use depends on the degree or intensity of use in the retrospective application. It is therefore not possible to provide a 'life

span' of the gloves.

Note Due to the nature of this product the user is advised to carry out their own risk assessment before use, depending on application.

Warning This product contains natural rubber latex which could cause anaphylactic responses.

