

Key information:

- Cut E, 13 gauge Polyester outer liner with a 7 gauge, Thermal, Acrylic, HPPE and Steel inner liner
- Fully Coated in Smooth Nitrile with Sandy Nitrile Palm finish
- Suitable for use inside or outside, in wet or dry; cold or warm conditions

- Superb wet or dry grip
- Contact Cold Level 2
- Contact Heat Level 2
- Elasticated, coloured cuff for size indication
- Extremely comfortable and dexterous











Code: WS5

Liner: Polyester/Acrylic HPPE/Steel

Size: 8 to 11

Gauge: 13/7

Coating Sandy Nitrile

Pack size: 5 pairs

Carton: 120 pairs

EN388: 4X43E

EN511: X21

EN407: X2XXXX

Applications include:

Cold Stores, Scaffolding, Construction, Transport, Maintenance, Local Authorities, Recycling, Engineering

Limitations of Use

Maintenance Examine gloves for damages, splits and holes before each use. Always replace damaged gloves. Only properly fitting gloves guarantee protection and grip.

Storage Store at normal room temperature in a dry, well ventilated area. Avoid direct heat radiation.

Disposal Used gloves can be contaminated. Dispose with household waste or as instructed by your local authority.

Cleaning Do not wash. The performance of the product after laundering is unknown. Beat or brush out after each use, depending on level of dirt.

DurabilityThe period of use depends on the degree or intensity of use in the retrospective application. It is therefore not possible to provide a 'life span' of the gloves.

NoteDue to the nature of this product the user is advised to carry out their own risk assessment before use, depending on application.

