



PRODUCT INFORMATION SHEET

These items were imported by: -

Just 1 Source & Supply Limited, Barton Hill, Whitwell, York. YO60 7JX Telephone: 01653 617718 - www.just1source.com

These items comply with the requirements of the PPE Regulation (EU)2016/425 and PPE Regulation (EU)2016/425 as brought into UK Law and amended, in line with the harmonised and designated standard(s) referenced below. **NOTE: -** Declarations of Conformity can be found at **www.just1source.com Limitations of use:**

EN 388:2016 + A1:2018, EN ISO 21420:2020 - The overall classification of gloves with two or more layers does not necessarily reflect the performance of the outermost layer. Gloves should not be worn when there is a risk of entanglement by moving parts or machinery.

The EN 388 test results shown below are taken from the palm area of the glove

NOTE: Due to the nature of this product the user is advised to carry out their own risk assessment depending on application

Temperature durations can be found under Annex B of the EN511 standard These gloves may lose their insulative properties when wet

EN 388:2016 + A1:2018





EN ISO 21420:2020

| Test | Performance Level | Test | Performance Level |
|-----------------------|----------------------|-------------------------------|----------------------|
| EN 388:2016 + A1:2018 | | EN511:2006 | |
| Abrasion | 4 (Scale 1-4) | Resistance to Convective Cold | X (Scale 0-4) |
| Blade Cut (Coup Test) | X (Scale 1-5) | | . , |
| Tear | 4 (Scale 1-4) | Resistance to Contact Cold | 2 (Scale 0-4) |
| Puncture | 3 (Scale 1-4) | | · · · · |
| ISO 13997 Cut (TDM) | E (Scale A-F) | Permeability by Water | 1 (Scale 0-1) |
| Impact Protection | (P if passed) | | . , |

| ISO Cut Level | Α | В | С | D | E | F |
|---------------|----|----|-----|-----|-----|-----|
| Newtons | ≥2 | ≥5 | ≥10 | ≥15 | ≥22 | ≥30 |

| EN511:2006 - Cold Protection | 0 | 1 | 2 | 3 | 4 |
|-----------------------------------|----------|------------|-------------|------------|-----------------------|
| A. Convective Cold | l <0.10 | 0.10 < l < | 0.15 < I | 0.22 < l < | 0.30 < I |
| Thermal Insulation ITR in m2.°C/W | | 0.25 | <0.22 | 0.30 | |
| B. Contact Cold | R <0.025 | 0.025 < R | 0.050 < R < | 0.100 < R | 0.150 <r< td=""></r<> |
| Thermal resistance R in m2.°K/W | | <0.050 | 0.100 | < 0.15 | |
| C. Water Penetration Test | Fail | Pass | - | - | - |

Performance levels are measured where the highest number indicates the best protection.

"X" indicates that the product has not been tested against this risk

| Product Code: - | WS5 | Size: 8 - 11 |
|------------------------|----------------------|----------------------------------------------------|
| Product Name: - | Watersafe Arctic | |
| Braduat Departmention: | 12a Plue Polyastar O | uter Liner plue 7g Crey Aerulie Leep Inper Liner F |

Product Description: - 13g Blue Polyester Outer Liner plus 7g Grey Acrylic Loop Inner Liner, Double Coated Nitrile

Gloves providing protection against mechanical risks.

- Maintenance: examine gloves for damages, splits and holes before each use. Always replace damaged gloves.
- Disposal Dispose of used gloves as instructed by your local authority

STORAGE: Store in dry ambient conditions

AFTERCARE: No Cleaning Treatment

CE

EU Type Certification issued by **CTC**, 4 Rue Hermann Frenkel, 69367 LYON, Cedex 07, FRANCE – *Notified Body 0075*



UK Type Certification issued by **ITS Testing Services** (**UK**) Ltd, Centre Court, Meridian Business Park, Leicester. LE19 1WD – Approved Body AB 0362

