



PRODUCT INFORMATION SHEET

These items were imported by: Just 1 Source & Supply Limited, Barton Hill, Whitwell, York. YO60 7JX
Telephone: 01653 617718 - www.just1source.com

These items comply with the requirements of the EU Regulation 2016/425 & Regulation 2016/425 on personal protective equipment, as amended to apply in GB, in line with the harmonised and designated standard(s) referenced below.

NOTE: - Declarations of Conformity can be found at www.just1source.com

Limitations of use:

EN 388:2016 + A1:2018, EN 511:2006, EN407:2020, EN ISO 21420:2020 - The overall classification of gloves with two or more layers does not necessarily reflect the performance of the outermost layer.

Gloves should not be worn when there is a risk of entanglement by moving parts or machinery.

The gloves protect part of the hand only.

The EN 388 test results shown below are taken from the palm area of the glove.

NOTE: Due to the nature of this product the user is advised to carry out their own risk assessment depending on application

Temperature durations can be found under Annex B of the EN511 standard.

These gloves may lose their insulative properties when wet.

EN 388:2016 + A1:2018



4X43E

EN 511:2006



X21

EN 407:2020



X2XXXX

EN ISO 21420:2020



Test	Performance Level	Test	Performance Level
EN 388:2016 + A1:2018		EN511:2006	
Abrasion	4 (Scale 1-4)	Resistance to Convective Cold	X (Scale 0-4)
Blade Cut (Coup Test)	X (Scale 1-5)		, ,
Tear	4 (Scale 1-4)	Resistance to Contact Cold	2 (Scale 0-4)
Puncture	3 (Scale 1-4)		,
ISO 13997 Cut (TDM)	E (Scale A-F)	Permeability by Water	1 (Scale 0-1)
Impact Protection	(P if passed)		, , ,

Test	Performance Level	
EN 407:2020		
Burning Behaviour	X (Scale 0-4)	
Contact Heat	2 (Scale 0-4)	
Convective Heat	X (Scale 0-4)	
Radiant Heat	X (Scale 0-4)	
Small Molten Splash	X (Scale 0-4)	
Large Molten Splash	X (Scale 0-4)	

ISO Cut Level	Α	В	С	D	E	F
Newtons	≥2	≥5	≥10	≥15	≥22	≥30

EN511:2006 - Cold Protection	0	1	2	3	4
A. Convective Cold	I <0.10	0.10 < l <	0.15 < I	0.22 < l <	0.30 < I
Thermal Insulation ITR in m2.°C/W		0.25	<0.22	0.30	
B. Contact Cold	R <0.025	0.025 < R	0.050 < R <	0.100 < R	0.150 <r< td=""></r<>
Thermal resistance R in m2.°K/W		<0.050	0.100	< 0.15	
C. Water Penetration Test	Fail	Pass	-	-	-

Performance levels are measured where the highest number indicates the best protection.

[&]quot;X" indicates that the product has not been tested against this risk





Product Code: -**WS5** Size: 8 - 11

Product Name: -**Watersafe Arctic**

Product Description: -13g Blue Polyester Outer Liner plus 7g Grey Acrylic Loop Inner Liner,

Double Coated Nitrile

Gloves providing protection against mechanical risks and protection against cold. Maintenance: examine gloves for damages, splits and holes before each use. Always replace damaged gloves.

The Gloves do not contain any substances know to cause allergic reaction.

To put the glove on, pull over the top of the hand inserting the fingers and thumb into the applicable pouch, use the cuff to pull down securely over the hand to ensure that there is no excessive gap between the inside of the glove fingers and fingertips. To remove the glove, pull away from the top of the glove fingers.

> STORAGE: Store in dry ambient conditions AFTERCARE: No Cleaning Treatment



EU Type Certification issued by CTC, 4 Rue Hermann Frenkel, 69367 LYON, Cedex 07, FRANCE - Notified Body 0075



UK Type Certification issued by ITS Testing Services (UK) Ltd, Centre Court, Meridian Business Park, Leicester. LE19 1WD – Approved Body AB 0362



