

Key information:

Anti Vibration Glove

High Quality Black Goat ski Leather

Black Knitted Fleece for additional comfort

Black Elastic Wristband with Velcro Closure EN ISO 10819:2013 + A1:2019 The test is performed in one-third octave frequency bands with the centre frequencies of 25Hz to 1250Hz.

The following criteria must be achieved to be classed as an Anti-Vibration Glove:

TM value shall be less or equal to ≤ 0.9 (total vibration transmission between 25Hz – 200Hz)

TH value shall be less or equal to ≤ 0.6 (total vibration transmission between 200Hz – 1250Hz) EN388:2016 + A1:2018 N ISO 10819:2013 +A1:2019

TM 0,731

UK CA



Code: PRED16 Size: 7-11 Pack size: 5 pairs

Carton: 40 pairs

EN388:2016 + A1:2018 3122X

Applications include:

Any application where vibration is present, Concrete Breakers, Construction, Engineering, Jack Hammer, Mining

Limitations of Use

Maintenance Examine gloves for damages, splits and holes before each use. Always replace damaged gloves. Only properly fitting gloves

guarantee protection and grip.

Storage Store at normal room temperature in a dry, well ventilated area. Avoid direct heat radiation.

Disposal Used gloves can be contaminated. Dispose with household waste or as instructed by your local authority.

Cleaning Do not wash. The performance of the product after laundering is unknown. Beat or brush out after each use, depending on level of

dirt.

DurabilityThe period of use depends on the degree or intensity of use in the retrospective application. It is therefore not possible to provide

a 'life span' of the gloves.

Note Due to the nature of this product the user is advised to carry out their own risk assessment before use, depending on application.

