

PRED ANTI-VIBE

PRED16



Key information:

Anti Vibration Glove

High Quality Black Goat skin
Leather

Black Knitted Fleece for
additional comfort

Black Elastic Wristband with
Velcro Closure

EN ISO 10819:2013 + A1:2019
The test is performed in one-third
octave frequency bands with the centre
frequencies of 25Hz to 1250Hz.

The following criteria must be achieved
to be classed as an Anti-Vibration Glove:

TM value shall be less or equal to ≤ 0.9
(total vibration transmission between
25Hz – 200Hz)

TH value shall be less or equal to ≤ 0.6
(total vibration transmission between
200Hz – 1250Hz)

EN388:2016
+ A1:2018



3122X

EN ISO 10819:2013
+A1:2019



TM 0,731

TH 0,571

UK
CA
CE



Code: PRED16

Size: 7-11

Pack size: 5 pairs

Carton: 40 pairs

EN388:2016
+ A1:2018 3122X

Applications include:

Any application where vibration is present, Concrete Breakers, Construction, Engineering, Jack Hammer, Mining

Limitations of Use

Maintenance	Examine gloves for damages, splits and holes before each use. Always replace damaged gloves. Only properly fitting gloves guarantee protection and grip.
Storage	Store at normal room temperature in a dry, well ventilated area. Avoid direct heat radiation.
Disposal	Used gloves can be contaminated. Dispose with household waste or as instructed by your local authority.
Cleaning	Do not wash. The performance of the product after laundering is unknown. Beat or brush out after each use, depending on level of dirt.
Durability	The period of use depends on the degree or intensity of use in the retrospective application. It is therefore not possible to provide a 'life span' of the gloves.
Note	Due to the nature of this product the user is advised to carry out their own risk assessment before use, depending on application.