

Key information:

- 13g Green Ultra High Molecular Weight Polyethylene/Spandex Liner
- Cut Level D
- Additional Thumb Crotch Protection
- Touchscreen Capability
- Robust sandy nitrile palm coating
- Contact Heat Level 1
- Header Carded product



Code: SN13DTQ

Liner: UHMWPE/ Spandex

Size: 6 to 11

Gauge: 13

Coating: Sandy Nitrile

Carton: 120 Pairs

EN388:2016 + A1:2018 4X42D

EN407:2020 X1XXXX

Applications include:

Agriculture, Construction, Cut Risk Areas, Engineering, Glass Handling, Metal Handling

Limitations of Use

Maintenance Examine gloves for damages, splits and holes before each use. Always replace damaged gloves. Only properly fitting gloves guarantee protection and grip.

Storage Store at normal room temperature in a dry, well ventilated area. Avoid direct heat radiation.

Disposal Used gloves can be contaminated. Dispose with household waste or as instructed by your local authority.

Cleaning Do not wash. The performance of the product after laundering is unknown. Beat or brush out after each use, depending on level of dirt.

Durability The period of use depends on the degree or intensity of use in the retrospective application. It is therefore not possible to provide a 'life span' of the gloves.

Note Due to the nature of this product the user is advised to carry out their own risk assessment before use, depending on application.



Hands Protected; Work Perfected