

## **Key information:**

- 15 gauge Nylon/Spandex Liner
- Superb Quality Nitrile Micro Foam Palm Coating
- Contact Heat Level 1
- Second skin feel with high breathability liner
- Cut Level 1
- Elasticated cuff with coloured cuff size indicator



Code: MF15A
Liner: Nylon/Spandex
Size: 6-11
Gauge: 15

Nitrile Micro
Coating: Foam Palm
Coating

Carton: 120 Pairs EN 388:2016 + A1:2018 4131A

10 Pairs

Pack Size:

EN407:2020 X1XXXX

## **Applications include:**

Construction, Engineering, General Handling, Landscaping, Packaging, Scaffolding, Warehousing

## **Limitations of Use**

Maintenance Examine gloves for damages, splits and holes before each use. Always replace damaged gloves. Only properly fitting gloves guarantee protection and grip.

**Storage** Store at normal room temperature in a dry, well ventilated area. Avoid direct heat radiation.

**Disposal** Used gloves can be contaminated. Dispose with household waste or as instructed by your local authority.

**Cleaning** Do not wash. The performance of the product after laundering is unknown. Beat or brush out after each use, depending on level of dirt.

**Durability** The period of use depends on the degree or intensity of use in the retrospective application. It is therefore not possible to provide a 'life span' of the gloves.

**Note** Due to the nature of this product the user is advised to carry out their own risk assessment before use, depending on application.

