

PRODUCT INFORMATION SHEET

These items were imported by: -
Just 1 Source & Supply Limited, Barton Hill, Whitwell, York. YO60 7JX
Telephone: 01653 617718 - www.just1source.com

These items comply with the requirements of the EU Regulation 2016/425, in line with the harmonised standard(s) referenced below.

NOTE: - Declarations of Conformity can be found at www.just1source.com

Limitations of use:

EN 388:2016 + A1:2018, EN ISO 21420:2020 - The overall classification of sleeves with two or more layers does not necessarily reflect the performance of the outermost layer. Sleeves should not be worn when there is a risk of entanglement by moving parts or machinery.

The EN 388 test results shown below are taken from a section of the sleeve

Warning: This product is not intended as a replacement for welding sleeves

EN 388:2016 + A1:2018



2X4XD

EN ISO 21420:2020



Test	Performance Level
EN 388:2016 + A1:2018	
Abrasion	2 (Scale 1-4)
Blade Cut (Coup Test)	X (Scale 1-5)
Tear	4 (Scale 1-4)
Puncture	X (Scale 1-4)
ISO 13997 Cut (TDM)	D (Scale A-F)
Impact Protection	(P if passed)

ISO Cut Level	A	B	C	D	E	F
Newtons	≥2	≥5	≥10	≥15	≥22	≥30

Performance levels are measured where the highest number indicates the best protection.
"X" indicates that the product has not been tested against this risk

Product Code: - **SL2CLD** Size: **45 cm**
Product Name: - **Pred Python**
Product Description: - **18-gauge Nylon/Metal Q/Spandex Cut Resistant Sleeve – Cut Level D**

Sleeves provide protection against mechanical risks.

Maintenance: examine sleeves for damages, splits and holes before each use. Always replace damaged sleeves.

Disposal – Dispose of used sleeves as instructed by your local authority

STORAGE: Store in dry ambient conditions **AFTERCARE:** No Cleaning Treatment

 EU Type Certification issued by **CTC**, 4 Rue Hermann Frenkel, 69367, LYON,
Cedex 07, FRANCE - **Notified Body 0075**