

PRODUCT INFORMATION SHEET

These items were imported by: -
Just 1 Source & Supply Limited, Barton Hill, Whitwell, York. YO60 7JX
Telephone: 01653 617718 - www.just1source.com

These items comply with the requirements of the EU Regulation 2016/425, in line with the harmonised standard(s) referenced below.

NOTE: - Declarations of Conformity can be found at www.just1source.com

Limitations of use:

EN 388:2016 + A1:2018, EN ISO 21420:2020 - The overall classification of gloves with two or more layers does not necessarily reflect the performance of the outermost layer. Gloves should not be worn when there is a risk of entanglement by moving parts or machinery.

The EN 388 test results shown below are taken from the palm area of the glove.

EN 388:2016 + A1:2018



2141A

EN ISO 21420:2020



Test	Performance Level
EN 388:2016 + A1:2018	
Abrasion	2 (Scale 1-4)
Blade Cut (Coup Test)	1 (Scale 1-5)
Tear	4 (Scale 1-4)
Puncture	1 (Scale 1-4)
ISO 13997 Cut (TDM)	A (Scale A-F)
Impact Protection	(P if passed)

ISO Cut Level	A	B	C	D	E	F
Newton's	≥2	≥5	≥10	≥15	≥22	≥30

Performance levels are measured where the highest number indicates the best protection.
"X" indicates that the product has not been tested against this risk

Product Code: - **LCPL-RED** Size: **6-11**
Product Name: - **PRED Fire**
Product Description: - 13 Gauge Polyester Liner with a Crinkle Latex Palm Coating

Gloves provide protection against mechanical risks.

Maintenance: examine gloves for damage, splits and holes before each use. Always replace damaged gloves.

Disposal – Dispose of used gloves as instructed by your local authority

WARNING: This product contains natural rubber latex which could cause anaphylactic responses

STORAGE: Store in dry ambient conditions AFTERCARE: No Cleaning Treatment

 EU Type Certification issued by **TUV SUD Danmark**, Strandvejen 125, 2900 Hellerup, Denmark - **Notified Body 2443**