



Product Information Sheet



Product Name: **Pred Needle**

Product Category: **Specialist**

Product Code: **PRED12**

Sizes: **8-11**

Product Description: **Black Poly Cotton & Steel Liner; Fully Coated Black Crinkle Latex with Velcro wrist fastening**

These gloves were imported by: Just 1 Source & Supply Limited, York, YO60 7JX, UK

Telephone: 01653 617 7118 Website: www.just1source.com

These items comply with the requirements of the EU Regulation 2016/425, in line with the harmonised standard(s) referenced below.



Please scan this QR Code to view the Declarations of Conformity

Limitations of use

EN 388:2016 + A1:2018, EN ISO 21420:2020 - The overall classification of gloves with two or more layers does not necessarily reflect the performance of the outermost layer. Gloves should not be worn when there is a risk of entanglement by moving parts or machinery.

Note – Declarations of Conformity can be found at www.just1source.com

**EN388:2016
+A1:2018**



3X44F

**EN ISO 21420
:2020**



Glove is not washable



The EN 388 test results shown below are taken from the palm area of the glove								
EN388:2016 +A1:2018	Performance Level	Performance Levels	0	1	2	3	4	5
Abrasion (Scale 1-4)	3	Abrasion Resistance <i>Number of cycles(minimum)</i>	<100 0	100	50 0	2000	8000	n/a
Blade Cut (Coupe Test) (Scale 1-5)	X	Blade Cut <i>(Coupe Test) - Minimum</i>	<1.2	1.2	2. 5	5.0	10.0	20.0
Tear (Scale 1-4)	4	Tear Resistance <i>Force (N) (Minimum)</i>	<10	10	25	50	75	n/a
Puncture (Scale 1-4)	4	Puncture Resistance <i>Force (N) (Minimum)</i>	<20	20	60	100	150	n/a
ISO 13997 (TDM) (Scale A-F)	F	ISO Cut Level <i>(N)</i>	A	B	C	D	E	F
Impact Protection (P for Pass)	Not Tested		2	5	10	15	22	30

WARNING: This product contains natural rubber latex which could cause anaphylactic responses.

This product has been tested in accordance with ANSI 105-2016 – Hypodermic Needle Puncture Resistance (ASTM F2878 – 2019) – Result: Level 5						
Performance Level	0	1	2	3	4	5
ANSI/ISEA 105-2016	<2	≥2	≥4	≥6	≥8	≥10
PRED12 Result						33.8

Disposal: Dispose of used gloves as instructed by your local authority

Maintenance: Examine gloves for damages, splits and holes before each use. Always replace damaged gloves. Gloves may lose their insulative properties when wet. Due to the nature of this product the user is advised to carry out their own risk assessment.

Donning: Insert all five fingers into the cuff of the glove and pull the cuff over your wrist until the glove is properly in place. Make sure the cuff is pulled up fully to avoid any substances or debris entering the glove.

Doffing: Pinch and lift the outside of the glove in the palm area with the opposite gloved hand; peel off while turning inside out. Hold the removed glove in the gloved hand. Slide two fingers of the ungloved hand under the remaining glove at the wrist. Peel the second glove off over the first glove and discard.

Storage: Store in dry ambient conditions, storage will not change the gloves characteristics significantly

Allergic Reactions: These gloves may cause allergic reactions, in the case of an allergic reaction please discontinue use immediately and seek medical advice. A list of substances is available on request.

Obsolescence: The shelf life of this product cannot be determined due to nature of the materials used in the composition of product, as it will be affected by many factors, such as storage conditions, usage etc.

Intended Use: This glove offers the highest level of cut protection, tear & puncture resistance as well as achieving Level 5 for Hypodermic Needle Resistance. Ideal for use in Glass Handling, High-Pressure Cut Applications, Metal Handling, Needle Stick, Refuse & Sharps.



EU Type Certification issued by **SATRA Technology Europe Ltd**, Bracetown Bus Park, Clonee, Dublin 15 Ireland – **Notified Body 2777**